



PRODUCT-DETAILS

XT2N 160 Ekip Dip LS/I In=160A 3p F F

XT2N 160 Ekip Dip LS/I In=160A 3p F F



General Information	
Extended Product Type	XT2N 160 Ekip Dip LS/I In=160A 3p F F
Product ID	1SDA067058R1
EAN	8015644007959
Catalog Description	XT2N 160 Ekip Dip LS/I In=160A 3p F F
Long Description	C.BREAKER TMAX XT2N 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 160 A

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 55.70 %
End of Life Instructions	9AKK108468A2349

Group Waste to Landfill
Target

UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD	9AKK108469A1855 9AKK108468A1897
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

SCIP b90612d8-2735-48c0-a56d-dc45be673814 Italy (IT)

Simplified SCIP 83bd7a2a-eec9-46f1-b3c9-2121e7990084 Germany (DE)
 f169be50-7e04-4524-ab8e-7ce1763b47b9 France (FR)
 ad6d175f-75d5-4039-b30b-6180d39af189 Norway (NO)
 32f4ada9-55a6-4949-bb23-bbaf1b1ddd00 Finland (FI)
 639d2250-1084-4545-9b47-11f4136ba1de Netherlands (NL)
 5d932a2c-9f30-4e07-af0d-e9c67e6fbae8 Germany (DE)
 da1187e6-35c6-4fcf-98f5-45b8b5524dee Denmark (DK)
 d52e6c34-7d2f-417c-adcd-298010509da7 Germany (DE)
 fef67e1e-b863-4d26-8eda-30b19f23c531 Netherlands (NL)
 eacfccbb-a82d-4fac-bd44-f90b918e6b2f Spain (ES)
 378fd1f0-ddca-4b7b-812e-066cfa35bc3b Netherlands (NL)
 75555083-4fe1-495b-aa08-52ad3b730e2f Germany (DE)
 2a8dc798-9ad8-4510-8e26-c7eb48a964e9 Poland (PL)
 b08cf1d0-f1be-4019-956a-2f6676f2f0bb Croatia (HR)
 7aef0e65-8b0f-440a-92b4-e47d31bdb3df Czech Republic (CZ)
 0b7af615-fe02-435b-b2e5-ac5781d752ab Poland (PL)
 b9ee9955-ee43-4015-99a5-02af016b3924 Netherlands (NL)
 c0de57ed-ce97-45a9-9eb5-9e93d59bf892 Netherlands (NL)
 781f0e8d-1411-44b0-a834-5ebc37831338 Estonia (EE)
 8296011d-d5f0-4f2d-8fbc-93eb75957b38 Greece (GR)
 b0bc9672-0156-4859-94ec-587cd5d95f50 Portugal (PT)
 3dc9bc4b-1e87-4ae9-967b-958d8fae4481 Bulgaria (BG)
 48b1023d-77c4-4afd-a4fc-7e4e3da8817d Sweden (SE)
 7b86cf23-28b1-4ecc-af6e-5fd68920903c Poland (PL)
 38658003-4bce-41db-918e-b155d51dd413 Sweden (SE)
 bdc04d42-017e-4f67-871a-3cadf5ac1440 Germany (DE)
 44da1b16-8c2b-4c4e-a9c1-9553a48028de France (FR)

Ordering

Order Code US and Canada	XT2NE3160EFF000XXX
E-Number (Finland)	3638188
E-Number (Sweden)	3182027
EAN	8015644007959

Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	90 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.4 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Height	208 mm
Package Level 1 Depth / Length	145 mm
Package Level 1 Gross Weight	1.71 kg
Package Level 1 EAN	8015644007959
Package Level 2 EAN	8015644007959

Additional Information

Brand / Label	ABB
Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH002230A1001

Technical

Connecting Capacity Main Circuit	Busbar 32.5..100 mm ²
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 10.8 W
Rated Current (I _n)	160 A
Rated Frequency (f)	50 / 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	8 kV

Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 65 kA (230 V AC) 65 kA (240 V AC) 65 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 10 kA
Rated Uninterrupted Current (I _u)	160 A
Rated Voltage (U _r)	690 V
Recommended Screw Driver	Main Circuit M6
Release	Ekip Dip LS/I
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC60947-2
Sub-type	XT2
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m

Certificates and Declarations

ABS Certificate	1SDL000163R0109
ATEX Certificate	No certification needed
BV Certificate	1SDL000163R0099
CB Certificate	9AKK106713A2843
CQC Certificate	CQC2013010307643219 CQC2013010307650258 CQC2018010307082330
Data Sheet, Technical Information	SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CCC	9AKK108466A7755 2020980307003311 2020980307003400
Declaration of Conformity - CE	9AKK106713A5901
DNV GL Certificate	1SDL000163R0096
EAC Certificate	9AKK10103A1027
GL Certificate	1SDL000163R0093
I ² t Characteristic	1SDC210099D0206
KC Certificate	HW05022-15105
LR Certificate	1SDL000163R0100

RINA Certificate	1SDL000163R0098
UL Certificate	1SDL000163R0112
VDE Certificate	No certification needed
Dimension Diagram	1SDH000721R0100
Mechanical Drawings	1SDH000721R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000721R0001

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4932 >> 3 Pole Non-Interchangeable Trip Electronic Circuit Breakers
Object Classification Code	Q
UNSPSC	39121616
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

