



PRODUCT-DETAILS

XT5H 400 Ekip Dip LSIG In=400 3p F F

XT5H 400 Ekip Dip LSIG In=400 3p F F



General Information	
Extended Product Type	XT5H 400 Ekip Dip LSIG In=400 3p F F
Product ID	1SDA100498R1
EAN	8056221005753
Catalog Description	XT5H 400 Ekip Dip LSIG In=400 3p F F
Long Description	C.BREAKER TMAX XT5H 400 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 400

ABB EcoSolutions	
ABB EcoSolutions	Yes

Circular Value	
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 59.6 %
End of Life Instructions	9AKK108468A2354

Group Waste to Landfill
Target

UL 2799 Zero Waste To Landfill Validation available

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1899 9AKK108468A9748
---	------------------------------------

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Ordering

Order Code US and Canada	XT5HE340AGFF000XXX
EAN	8056221005753
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.82 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	250 mm
Package Level 1 Height	245 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	5.308 kg
Package Level 1 EAN	8056221005753

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH002065A1115 1SDH002065A1131

Technical

Current Type	AC
Electrical Durability	120 cycles per hour 7000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	3
Order Multiple	1 piece
Power Loss	19 W
Rated Current (I _n)	400 A
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 40 kA
Rated Short-time Withstand Current Low Voltage (I _{cw})	5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 100 kA (230 V AC) 100 kA (240 V AC) 100 kA (380 V AC) 70 kA (415 V AC) 70 kA (440 V AC) 65 kA (500 V AC) 50 kA (525 V AC) 50 kA (690 V AC) 40 kA
Rated Uninterrupted Current (I _u)	400 A
Release	Ekip Dip LSIG
Release Type	EL
Short-Circuit Performance Level	H
Standards	IEC60947-2
Sub-type	XT5
Terminal Connection Type	Front

Certificates and Declarations

Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK107680A2824
Mechanical Drawings	1SDH002011A1101
Wiring Diagram	1SDM000005A1001
Instructions and Manuals	1SDH002011A1001

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

